



ROUND TUBES ASTM A249, A270 - EN 10217-7
Tubi tondi ASTM A249, A270 - EN 10217-7

outside diameter		Birmingham Wire Gauge				
		18	16	14	12	11
		wall thickness mm				
		1,24	1,65	2,11	2,77	3,05
mm	inches	weight kg/m				
15,88	5/8"	0,455	0,588	0,728		
19,05	3/4"	0,553	0,719	0,895		
25,4	1"	0,750	0,981	1,231	1,570	1,707
31,8	1 1/4"	0,949	1,246	1,569	2,014	2,196
38,1	1 1/2"	1,144	1,506	1,902	2,451	2,677
44,45	1 3/4"	1,342	1,768	2,237	2,891	3,162
50,8	2"	1,539	2,031	2,573	3,331	3,647
60,3	2 3/8"	1,834	2,423	3,074	3,990	4,372
63,5	2 1/2"	1,933	2,555	3,244	4,212	4,617
76,2	3"	2,327	3,080	3,915	5,093	5,587
88,9	3 1/2"		3,605	4,585	5,974	6,557
101,6	4"		4,130	5,256	6,855	7,526
114,3	4 1/2"		4,654	5,927	7,736	8,496



ROUND TUBES EN 10357 ex DIN 11850
Tubi tondi EN 10357 ex DIN 11850

weight
kg/m

outside diameter mm	wall thickness mm			
	1	1,5	1,6	2
18	0,426	0,620		
19		0,657		
22	0,526	0,770		
23		0,808		
25	0,715			
28	0,676	0,995		
29		1,033		
33		1,183		
34	0,826	1,221		
35		1,258		
38	1,106	1,371	1,458	
40	0,977	1,446		
41		1,484		
43		1,559		
50,8	1,490	1,852	1,971	
51	1,496			
52	1,277	1,897		
53		1,934		
63,5		2,329	2,480	
70				3,405
76,1		2,802	2,985	
85				4,157
101,6				4,988
104				5,108
129				6,360
154				7,612
204				10,116