



## SQUARE TUBES

Tubi quadri

weight  
kg/m

external dimensions	wall thickness mm							
	1	1,2	1,5	2	2,5	3	4	5
A x A mm								
10 x 10	0,294	0,347	0,422					
15 x 15	0,453	0,538	0,661	0,857				
16 x 16	0,485	0,576	0,709	0,921				
20 x 20	0,613	0,729	0,901	1,176				
25 x 25	0,772	0,921	1,140	1,495	1,837	2,167		
30 x 30	0,932	1,112	1,379	1,814	2,236	2,645		
35 x 35	1,091	1,304	1,618	2,133	2,635	3,124		
40 x 40	1,251	1,495	1,858	2,452	3,033	3,602	4,703	
45 x 45	1,410	1,686	2,097	2,771	3,432	4,081	5,341	
50 x 50		1,878	2,336	3,090	3,831	4,559	5,979	7,349
60 x 60			2,814	3,728	4,628	5,516	7,255	8,943
70 x 70			3,293	4,366	5,426	6,473	8,531	10,538
80 x 80			3,771	5,004	6,223	7,430	9,807	12,133
100 x 100			4,728	6,279	7,818	9,344	12,359	15,323
120 x 120				7,555	9,413	11,258	14,910	18,513
150 x 150				9,469	11,805	14,129	18,738	23,298
200 x 200				12,659	15,793	18,913	25,118	31,272
250 x 250						23,698	31,497	39,247



## SQUARE TUBES ASTM A554

Tubi quadri ASTM A554

external dimensions		Birmingham Wire Gauge				
		18	16	14	11	7
		wall thickness mm				
		1,24	1,65	2,11	3,05	4,57
A mm	inches	weight kg/m				
12,7	1/2"	0,464	0,600			
19,05	3/4"	0,715	0,934	1,171		
25,4	1"	0,966	1,269	1,598	2,238	
31,75	1 1/4"	1,217	1,603	2,025	2,856	
38,1	1 1/2"	1,468	1,937	2,453	3,474	
50,8	2"	1,971	2,606	3,308	4,709	6,882
63,5	2 1/2"		3,274	4,162	5,945	8,734
76,2	3"		3,942	5,017	7,181	10,585
101,6	4"		5,279	6,727	9,652	14,288